

TX-3100E Series

www.posiflex.com

POSIFLEX
Your Success is Our Vision



TX-3100E

TX-3100E Series

Advanced Fan-Free POS System

Key Features

- ▶ Equipped with Intel Pine View Dual Core D525 1.8 GHz (TX-3100E series) and DDR3 memory
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ Wide range of I/O supports for various applications
- ▶ Compact size and wall mount capability for easy space arrangement
- ▶ Rear cable cover for safety and neat outlook (Except TX-3100S-E)

Specification	TX-3100E / 3100S-E
Processor	Intel Pine View D525 1.8 GHz / 1 M Cache CPU (Dual Core)
System Memory	DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB
Storage Device	2.5" SATA HDD or SSD (Optional)
Power Supply	12V DC power adaptor, 60W
Audio	Buzzer Only
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux
Connectivity	
LAN Port	10 / 100 / 1000 Mb
Serial Port	DB9 x3, RJ-45x1 (Optional RJ45 to DB9 cable) with 5V support on COM2/COM3/COM4 12V support on COM2/COM3
PS/2 Keyboard	Yes
Standard USB Port	4
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD monitor
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	270 x 253 x 86 (TX-3100E) 270 x 200 x 86 (TX-3100S-E)
Weight (N. W. in kg)	2.29
Environment	
Operation Condition	0°C ~ +40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C ~ +50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
SSD	8 GB Minimum
2nd VGA Port	Yes, 2nd VGA port can't coexist with COM4
Wall Mounting Kit	WB-6812
Certifications	



Posiflex delivers the fan-free TX-3100E series as advanced POS systems. The TX-3100E series come with modern and technical sensation. Their trim outline strike an impression upon first sight, and the aluminum die casting are adopted to show a glimpse of fashion and also enhance the thermal solution. Inside their compact figure, the TX-3100E series accommodate Dual Core D525 1.8 GHz CPU respectively, 2.5" HDD or SSD and a variety of connectivity like LAN, Serial, PS/2, USB, VGA and CR ports.

The TX-3100E series are flexible for space-sensitive retailers to deploy them.

Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2012 TX30Q3C1

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com