




Specification

Model	XT-6715+
Processor	Intel Pineview dual core D525 CPU, 1.8GHz, 1M Cache
System Memory	DDR3 800MHz, SO-DIMM x 1, max. 4GB, factory default 2GB
Storage Device	SATA storage x 2, factory default 320GB HDD x 1
Power Supply	12V DC power adaptor, 60W (Optional 80W when equipping with 2nd LCD display LM-3014 & LM-3015)
OS Support	Windows 7 / POSReady 7 / Windows XP Pro / POSReady 2009 / Linux per request
Display	
LCD Display	15" TFT LCD, 1024 x 768 resolution
Touch Function	Resistive touch
Brightness adjustment	By digital push button
Connectivity	
LAN Port	10 / 100 / 1000Mb x 2
Serial Port	DB9 x 3 + RJ45 x 1 with 5V/12V support on COM1 / COM2 / COM3 / COM4, RJ-45 to DB9 cable optional
Parallel Port	1, via optional conversion cable
UPS Port	Yes
Standard USB Port	5
Powered USB Port	Optional 24V x 1 and 12V x 2 via 8th generation base
Audio	Internal 2W speaker
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor
Mini-PCIe slot	Yes, for half size card
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	5.6
Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
SSD	8GB minimum
SA-105	Side Attachment for XT Series with 3 track MSR
SA-205	Side Attachment for XT Series with iButton
SA-305	Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor
LM-3010	9.7" 1024 x 768 rear-mount 2nd display for JIVA XT Series (VGA interface)
LM-3014	14" 1366 x 768 rear-mount wide screen 2nd display for JIVA XT Series (VGA interface)
LM-3015	15" 1024 x 768 rear-mount 2nd display for JIVA XT Series (VGA interface)
TM-3010	9.7" 1024 x 768 rear-mount resistive touch display for JIVA XT Series (VGA interface)
TM-3014	14" 1366 x 768 rear-mount resistive touch display for JIVA XT Series (VGA interface)
TM-3015	15" 1024 x 768 rear-mount resistive touch display for JIVA XT Series (VGA interface)
LM-6607	7" 800 x 480 rear-mount 2nd display for XT series (USB interface)
PD-2608UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-350UE	2 x 20 LCD, rear-mount, USB with Virtual COM support
PD-6607	7" color LCD graphical line display, rear-mount (USB interface)
WIFI	Internal mini-PCIe WIFI module with PIFA Antenna
Certifications	  

Design and Manufacturing In Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2014Q1C1

POSIFLEX

JIVA XT-6715+

Flexible! Powerful! Elegant!



POSIFLEX

POSIFLEX Technology (India) Pvt Ltd., (India HQ)
985, 1st A Main Rd, 4th Cross, New Thippasandra, Bangalore 560 075.
Tel : +91 80 4078 2700 E-mail : Sales@posiflexindia.com
Fax : +91 80 4153 6089 Http://www.posiflexindia.com

POSIFLEX Technology Inc. (Global HQ)
Add No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan

SINCE 1984

WWW.POSIFLEX.COM